

55 TON



4
WORK STATIONS

FOUR WORKSTATIONS:

- **Standard (3)** – Punch, Flat Bar Shear & Angle Shear
- **Open (1)** – Customize your ironworker with 10 optional Attachments
- 10 interchangeable Attachments available to tailor the Ironworker to your project. See pages 20 and 21 for options

POWER LINK

- Available with PowerLink™ System to increases your capabilities with our ever expanding line of Hydraulic Tools
- ANSI B11.5-1988(O2) Compliant Guarding
- ETL/UL Approved Controls
- Integrated E-Stop, Lock-out/Tag-out
- Optimized workstation heights for improved efficiency
- Electric foot pedals with integrated jog control
- Adjustable electric stoke control

SPECIFICATIONS	
Punch Rating (tons)	55
Punch Max. Capacity (in.)	1-1/16 diam. in 5/8 in Mild Steel
Angle Shear Max. Capacity (in.)	3 x 3 x 3/8 4 x 4 x 1/4
Flat Bar Shear Max. Capacity (in.)	3/8 x 14 1/2 x 12 3/4 x 4
Opt. Coper Notcher Max. Capacity (in.)	2-1/2 x 4 x 5/16
Standard Motor	5 HP 3 Ph 230V
Dimensions (in.)	55-1/25 x 44-1/2 x 36-1/25
Weight (lbs.)	2480

STOCK NUMBER	PRODUCT DESCRIPTION
IW55-1P230	55 Ton Ironworker 230V, 1Ph
IW55-3P208	55 Ton Ironworker 208V, 3Ph
IW55-3P230	55 Ton Ironworker 230V, 3Ph
IW55-3P460	55 Ton Ironworker 460V, 3Ph
IW55-3P575	55 Ton Ironworker 575V, 3Ph

STOCK NUMBER	PRODUCT DESCRIPTION
IW55-1P230-AC500	55 Ton Ironworker 230V, 1Ph with PowerLink
IW55-3P208-AC500	55 Ton Ironworker 208V, 3Ph with PowerLink
IW55-3P230-AC500	55 Ton Ironworker 230V, 3Ph with PowerLink
IW55-3P460-AC500	55 Ton Ironworker 460V, 3Ph with PowerLink
IW55-3P575-AC500	55 Ton Ironworker 575V, 3Ph with PowerLink