



IRONWORKERS

50 TON



FOUR WORKSTATIONS:

- **Standard (4)** – Punch, Flat Bar Shear, Angle Shear & Coper Notcher
- 9 additional Attachments available to convert the Punch Workstation to your specific needs. See pages 20 and 21 for options

POWER LINK

- Available with PowerLink™ System to increases your capabilities with our ever expanding line of Hydraulic Tools
- ANSI B11.5-1988(02) Compliant Guarding
- ETL/UL Approved Controls
- Integrated E-Stop, Lock-out/Tag-out
- Optimized workstation heights for improved efficiency
- Electric foot pedals with integrated jog control
- Adjustable electric stoke control

SPECIFICATIONS

Punch Rating (tons)	50
Punch Max. Capacity (in.)	1 diam. in 5/8 in Mild Steel
Angle Shear Max. Capacity (in.)	3 x 3 x 3/8 4 x 4 x 1/4
Flat Bar Shear Max. Capacity (in.)	1/2 x 10 3/4 x 4
Opt. Coper Notcher Max. Capacity (in.)	2 x 3 x 5/16
Standard Motor	5 HP 3 Ph 230V
Dimensions (in.)	54-1/2 x 36-3/4 x 36-1/8
Weight (lbs.)	2020

STOCK NUMBER

PRODUCT DESCRIPTION

IW50-1P230	50 Ton Ironworker 230V, 1Ph
IW50-3P208	50 Ton Ironworker 208V, 3Ph
IW50-3P230	50 Ton Ironworker 230V, 3Ph
IW50-3P460	50 Ton Ironworker 460V, 3Ph
IW50-3P575	50 Ton Ironworker 575V, 3Ph

POWER LINK

STOCK NUMBER

PRODUCT DESCRIPTION

IW50-1P230-AC500	50 Ton Ironworker 230V, 1Ph with PowerLink
IW50-3P208-AC500	50 Ton Ironworker 208V, 3Ph with PowerLink
IW50-3P230-AC500	50 Ton Ironworker 230V, 3Ph with PowerLink
IW50-3P460-AC500	50 Ton Ironworker 460V, 3Ph with PowerLink
IW50-3P575-AC500	50 Ton Ironworker 575V, 3Ph with PowerLink