

Features

- Pull chain switch
- SJT type 3 conductor, 12' long cord
- Steel hub/spider aluminum paddle blades
- Coated steel guards
- Meets OSHA standards
- Motor, blades, guard, and mount are packed and shipped in a single UPS-able carton.
- Made in U.S.A. with domestic and foreign components.



WALL
MOUNT



PEDESTAL

Motor Specifications

- 2-speed
- 1-Phase, 120V
- Ball bearing
- Frame size: 48
- Totally enclosed
- Permanent split capacitor
- Permanently lubricated
- 1/2" Shaft

DIMENSIONS	
24"	27" Diameter x 14.5" Depth
30"	33.5" Diameter x 14.5" Depth

Product Specifications

- Oscillating model oscillates in a 90° arc or can be locked in a fixed position
- Metal gears in the oscillating mechanism allow the fan to operate at a maximum 30° downward tilt

Standard Models

FAN TYPE		HIGH PERFORMANCE			STANDARD INDUSTRIAL			OSCILLATING		
MOTOR	HP	1/3			1/4			1/4		
	SPEEDS	2			2			2		
CFM / RPM	24"	4300 / 3900 1100 / 800			3800 / 3400 1100 / 800			3800 / 3400 1100 / 800		
	30"	5400 / 4700 1100 / 800			4300 / 3800 1100 / 800			4300 / 3800 1100 / 800		
COLOR		GRAY			GRAY			GRAY		
POLE ADJUSTMENT		52" to 78"			52" to 78"			52" to 78"		
WARRANTY		3 YEARS			1 YEAR			1 YEAR		
SIZE	TYPE of MOUNT	MFG CATALOG NUMBER	MFG MODEL NUMBER	WT. (LBS)	MFG CATALOG NUMBER	MFG MODEL NUMBER	WT. (LBS)	MFG CATALOG NUMBER	MFG MODEL NUMBER	WT. (LBS)
24"	Pedestal Mount	07990002	UHP 24-P	75	07962302	ACU 24-P	75	07964002	ACU 24-PO	79
	Wall Mount	07990202	UHP 24-W	45	07962402	ACU 24-W	45	07964102	ACU 24-WO	49
30"	Pedestal Mount	07990102	UHP 30-P	73	07962802	ACU 30-P	73	07964202	ACU 30-PO	82
	Wall Mount	07990602	UHP 30-W	48	07962902	ACU 30-W	48	07964302	ACU 30-WO	52