

MAGNETIC RETRIEVERS & MECHANICAL FINGERS

MAG-MATE®

■ Pocket Tools & Retrievers



Ideal for reaching behind, underneath or around machinery and/or difficult to reach areas. The Fixed Shaft and Telescoping Shaft Magnetic Retrievers feature several Magnet Head styles that include the Fixed Head, Single Ball Swivel Head and the Double Ball Swivel Hinge Head that allow for more control and functionality. Powerful Rare Earth magnet material, except where noted. All Rare Earth tools have a maximum temperature of 180°F (82°C).



Fixed Shaft Retrievers & Tools

Description	Lift - lbs (kg)	Shaft	Dia. (in)	Ln. (in)	Wt. (lbs)	Model No.
A Key chain retriever. Powerful Rare Earth magnet encased in an Aluminum Rod.	4.0 (1.815)	AL	3/8	2	0.03	KCR375
B Pen sized magnetic tool. Sturdy clip holds magnet firmly in pocket.	2.5 (1.134)	AL	5/16	6	0.06	906
C Phillips head screw driver on one end, magnet on the other end. Comes with pocket clip.	2.5 (1.134)	AL	5/16	5-1/4	0.06	145M
D Slotted head screw driver on one end, magnet on the other end. Comes with pocket clip.	2.5 (1.134)	AL	5/16	5-1/4	0.05	127M
E Double Ball Swivel Hinge Head. Non-conductive Nylon handle.	1.0 (0.453)	NY	5/16	8-1/4	0.05	909
F Precision ground carbide tip scribe is reversible. Magnet is located on the other end.	2.5 (1.134)	AL	5/16	5	0.05	92CLP

Telescoping Shaft Retrievers & Tools

Description	Lift - lbs (kg)	Shaft	Dia. (in)	Ln. (in)	Ext. (in)	Wt. (lbs)	Model No.
G Stainless steel pen sized pilot lighter with match holding alligator clip.	N/A	SS	1/4	7-1/2	25-1/2	0.07	PLO1
H Double Ball Swivel Hinge Head. Hex rod prevents magnet from swinging while in use.	7.5 (3.402)	ZP	1/2	17	26-1/2	0.36	927
I Double Ball Swivel Hinge Head. Hex rod prevents magnet from swinging while in use.	12.0 (5.444)	ZP	1/2	13	26	0.44	931
J Stainless steel pen sized tool for tiny jobs. Comes with pocket clip.	2.0 (0.908)	CP	5/16	5-1/2	25-1/2	0.07	240N
K Magnetic retriever w/ Single Ball Swivel Head and nonslip solvent-resistant comfort grip.	7.0 (3.176)	SS	5/8	8	35	0.19	925
L1	5.0 (2.268)	SS	3/8	6-1/2	32	0.14	923
L2 Magnetic retriever w/ fixed head and nonslip solvent-resistant comfort grip.	7.0 (3.176)	SS	5/8	6-1/2	32	0.18	924
L3	20.0 (9.072)	ZP	1-1/8	16-1/2	29	0.65	990SM
L4 Ex-long, heavy duty, magnetic retriever w/ fixed head & nonslip solvent-resistant comfort grip.	14.0 (6.351)	ZP/SS	5/8	23-1/2	50	0.42	926

Flexible/Bendable Shaft Retrievers & Tools

Description	Lift - lbs (kg)	Shaft	Dia. (in)	Ln. (in)	Wt. (lbs)	Model No.
M Rigid retrieving tool that becomes flexible by removing wire rod from the shaft.	1.5 (0.681)	ZP	5/16	18	0.18	918F
N Flexible retriever w/ fixed head and nonslip solvent-resistant comfort grip	8.0 (3.628)	ZP	1/2	21	0.25	921
O1 Flexible, dual purpose allows you to get in and around awkward spots. Bend shaft to a	3.0 (1.361)	ZP	3/8	20	0.31	928S
O2 permanent position or remove inside wire to snake into position.	7.0 (3.176)	ZP	5/8	20	0.35	929S
P Bendable retriever bends and holds its shape. Magnet is retracted until the button is pushed.	2.0 (0.908)	ZP	5/16	17	0.26	915RM
Q Flexible retriever has a spring shaft that allows it to snake through tight areas. The magnet is retracted until the button is pushed.	2.0 (0.908)	ZP	3/8	24	0.29	922RM
R1 Bendable copper shaft magnetic retriever. Fits into tight spots. Knurled aluminum handle.	3.0 (1.361)	CO	5/16	25	0.11	900WF
R2	0.5 (0.227)	CO	0.175	20	0.08	900WFT

Mechanical Finger Retrievers & Tools

Description	Lift - lbs (kg)	Shaft	Dia. (in)	Ln. (in)	Wt. (lbs)	Model No.
S Flexible two jaw mechanical finger with a spring/plunger handle control. Mechanical finger span of 1".	12	ZP	3/8	17	0.25	715CF
T1 Flexible four jaw mechanical finger with a spring/plunger handle control. Mechanical finger span of 1".	10	ZP	1/2	13-1/2	0.20	612
T2		ZP	1/2	23-1/2	0.30	622
U1 Rigid two jaw mechanical finger with a spring/plunger handle control. Mechanical finger span of 1".	12	ZP	3/16	8	0.15	708
U2		ZP	3/16	12	0.22	712

Shaft Material: AL = Aluminum, CO = Copper, CP = Chrome Plated Steel, NY = Nylon, SS = Stainless Steel & ZP = Zinc Plated Steel.

■ Lighted Magnetic Pick-up Tool



Rare Earth, telescoping, magnetic retriever with built in light.



Description	Lift - lbs (kg)	Shaft	Magnet (in.)	Magnet Head	Ln. (in.)	Wt. (lbs.)	Model No.
Lighted	22 (9.98)	Stainless Steel	11/16	Fixed	7-1/2 - 32	0.20	MRT910L

