

NEW!



## Miller Swivel Anchors with 360° rotation

***Revolutionary swivel design provides freedom of movement!***

### Miller Swivel Anchors with D-ring

- **Freedom of Movement** – Innovative swivel design provides 360° D-ring rotation and 180° flip while preventing accidental gate load/roll-out when in use.
- **Versatile Application Use** – Permanent and portable structure mount options for steel and concrete.
- **Multiple Anchorage Options** – Available in 5,000 lb (5K) and 10,000 lb (10K) ultimate tensile strength; 10K anchors can be used with SkyGrip® or TechLine™ Horizontal Lifeline kits.
- **Corrosion Resistance** – Available in zinc-plated steel or stainless steel construction.
- **Removable/Reusable** – The Swivel Hybrid Anchor combines the technology of the new Swivel Anchor and the Miller Grip™ Anchor, resulting in a high-strength Swivel Anchor that can be removed and simply re-installed in a new location.
- **Rated for up to a 310 lb (141 kg) worker.**
- **Meets all applicable OSHA and ANSI requirements.**



**10K Swivel Hybrid**  
RACSWH100Y



**10K Zinc Plated**  
RACSWY100S



**5K Steel Swivel**  
RACSWS100S-316



**5K Zinc Plated**  
RACSWY050S

### Miller Drop-Through Swivel Anchors

- **Overhead Use** – Anchor drops through a 1 3/4-in to 2-in diameter hole to provide a 5,000 lb overhead anchor.
- **Freedom of Movement** – Innovative swivel design provides 360° D-ring rotation while preventing accidental gate load/roll-out when in use.
- **Removable/Reusable Concrete Anchor** – Portable anchor can be removed and simply re-installed in a new location; designed for use in cured concrete with a compression strength of at least 3,000 psi (20.7 MPa).
- **Rated for up to a 310 lb (141 kg) worker.**
- **Meets all applicable OSHA and ANSI requirements.**



RACDTA-5K6/6FT

## Miller Swivel Anchors with D-ring

| SKU   | Description  | Weight          |
|---|--|-----------------|
| <b>10,000 lb (10K) Swivel Hybrid Anchor</b>         |  |                 |
| RACSWH100Y  | 10K Removable/reusable concrete anchor with swivel D-ring  | 2.1 lb (1.0 kg) |
| <b>10,000 lb (10K) Zinc-Plated Swivel Anchors</b>   |  |                 |
| RACSWY100N  | 10K zinc-plated swivel only (hardware not included)  | 1.4 lb (0.6 kg) |
| RACSWY100S  | 10K zinc-plated swivel anchor with steel mounting hardware   | 1.9 lb (0.9 kg) |
| RACSWY100C  | 10K zinc-plated swivel anchor with concrete mounting hardware  | 2.1 lb (1.0 kg) |
| RACSWY1SBA  | Steel mounting hardware only (swivel not included)   | N/A             |
| RACSWY1CSA  | Concrete mounting hardware only (swivel not included)  | N/A             |
| RACSWP100N-KIT                                      | Weld kit for RACSWY100N  | 2.3 lb (1.0 kg) |
| RACSWX100N  | Steel back plate for RACSWY100N (bolt not included)  | 1.7 lb (0.8 kg) |
| <b>5,000 lb (5K) Stainless Steel Swivel Anchors</b> |  |                 |
| RACSWS100N-316                                      | 5K stainless steel swivel only (hardware not included)   | 1.4 lb (0.6 kg) |
| RACSWS100S-316                                      | 5K stainless steel swivel anchor with stainless steel mounting hardware                                    | 2.0 lb (0.9 kg) |
| RACSWS100C-316                                      | 5K stainless steel swivel anchor with concrete mounting hardware<br>RACDNC-TOOL required (sold separately) | 1.9 lb (0.9 kg) |
| RACSWS1SBA-316                                      | Stainless steel mounting hardware only (swivel not included)   | N/A             |
| RACSWS1DNC-316                                      | Concrete mounting hardware only (swivel not included)  | N/A             |
| RACDNC-TOOL   | Concrete bolt assembly tool  | 0.7 lb (0.3 kg) |
| RACSWP100N-316                                      | Weld kit for RACSWS100N-316  | 3.7 lb (1.7 kg) |
| <b>5,000 lb (5K) Zinc-Plated Swivel Anchors</b>     |  |                 |
| RACSWY050N  | 5K zinc-plated swivel only (hardware not included)   | 0.8 lb (0.4 kg) |
| RACSWY050S  | 5K zinc-plated swivel anchor with steel mounting hardware  | 1.1 lb (0.5 kg) |
| RACSWY050C  | 5K zinc-plated swivel anchor with concrete mounting hardware   | 1.2 lb (0.5 kg) |
| RACSWY2SBA  | Steel mounting hardware only (swivel not included)   | N/A             |
| RACSWY2CSA  | Concrete mounting only (swivel not included)   | N/A             |

## Miller Drop-Through Swivel Anchors

| SKU             | Description  | Weight          |
|-----------------|--|-----------------|
| RACDTA-5K/6FT   | 6-ft. (1.8 m) 5K drop-through anchor with 4-in. (10 cm) round plate & swivel   | 1.6 lb (0.7 kg) |
| RACDTA-5K6/6FT  | 6-ft. (1.8 m) 5K drop-through anchor with 6-in. (15 cm) square plate & swivel  | 2.6 lb (1.2 kg) |
| RACDTA-5K12/6FT | 6-ft. (1.8 m) 5K drop-through anchor with 12-in. (30 cm) square plate & swivel | 9.0 lb (4.1 kg) |

**⚠** This equipment should only be used after reading the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.



by Honeywell

► Ask the Expert ... Ask Miller.

800/873-5242: Honeywell Technical Service

800/430-5490: Honeywell Customer Care

[www.millerfallprotection.com](http://www.millerfallprotection.com)

GET CONNECTED:



LMSAB

**Honeywell**