

Class 3 Eclipse™ Coat

Stock Number - C44129	Compliance Standards: ANSI/ISEA 107 Class 3, Level 2, ASTM F1891.							
	Garment Detail: Coats are set-in sleeve construction with full cut shoulder and 180 degree sleeve-to-body angle. The coat has a zippered storm fly front with snap closure and an attached hood-in-collar. Sleeve cuffs have hook and loop take-up straps. The coat has a full vented cape back with fall protection access and 2 front cargo pockets with closure.							
Garment Type: High visibility, liquid proof and flame and arc resistant.	Reflective Tape: 2" flame resistant silver glass bead tape is level 2 compliant.							
Sizes: S, M, L, XL, 2X, 3X, 4X								
Color: Fluorescent Orange-Red.	Configuration: Harness tape layout with 1 horizontal band on body, and 2 bands on each sleeve.							
Material: Fluorescent orange-red material is 10.3 oz./yd ² FR PVC on non-woven Nomex® with Thermo-Grid™ technology.	Garments/Tags: 1. Woven label sewn at neck displays Tingley logo and size. 2. Eclipse logo on sleeve cuff take-up. 3. Label sewn into left front hem displays ANSI/ISEA 107, ASTM F1891 and NFPA 70E compliance. Care instructions, fabric composition, lot and date codes are located on the reverse. 4. Label sewn into left front hem displays warning/disclaimer. 5. Name tag is sewn into left front hem. 6. Job Sight FR™ brand and HRC 2 heat transfer label on right pocket closure flap. 7. Printed hangtag with style, size, UPC bar code and noting high visibility, waterproof, and flame and arc resistance.							
Seam Construction: All seams are 100% waterproof RF/heat sealed lap construction.								
Closure Type: Zippered storm fly front with concealed snap closure system.	Packaging: Printed polyethylene bag.							
Pockets: 2 front cargo pockets with flap, and hook and loop closures.	Other: Thermal Performance conforms to ASTM F1891, Test Method ASTM F1959. Eclipse Yellow-Green ARC Rating: 11 cal/cm ² . NFPA 70E HRC 2.							
Dimensions	S	M	L	XL	2X	3X	4X	
Chest	46"	50"	54"	58"	62"	66"	70"	
Length	47"	48"	50"	50"	52"	52"	52"	
Sleeve Length	36"	36"	36.5"	37"	37.5"	38"	38"	
Case Pack: 12 each								
Case Dimensions/Weight								
S = 15"(L) X 13"(W) X 14"(H) / 37 lbs.		2X = 15"(L) X 13"(W) X 14"(H) / 46 lbs.						
M = 15"(L) X 13"(W) X 14"(H) / 40 lbs.		3X = 15"(L) X 13"(W) X 14"(H) / 48 lbs.						
L = 15"(L) X 13"(W) X 14"(H) / 42 lbs.		4X = 15"(L) X 13"(W) X 14"(H) / 51 lbs.						
XL = 15"(L) X 13"(W) X 14"(H) / 44 lbs.								

Eclipse™, Thermo-Grid™ and Job Sight FR™ are trademarks of Tingley Rubber Corp.

Nomex® is a registered trademark of E. I. du Pont de Nemours and Co.