



3/8" DRIVE DEEP IMPACT SOCKETS, 6 POINT, METRIC

Black Industrial Finish

Product Code	Size (MM)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)
12M-607	7	2 1/8	11/16	7/16	9/32	1 11/16	1/4	1 1/8
12M-608	8	2 1/8	11/16	1/2	1/4	1 11/16	9/32	1 1/8
12M-609	9	2 1/8	11/16	9/16	9/32	1 11/16	1 1/32	1 1/8
12M-610	10	2 1/8	11/16	5/8	9/32	1 11/16	1/32	1 1/8
12M-611	11	2 1/8	11/16	21/32	21/64	1 11/16	1 1/32	1 1/8
12M-612	12	2 1/8	23/32	23/32	3/8	1 23/32	7/16	-
12M-613	13	2 1/8	25/32	25/32	7/16	1 3/8	15/32	-
12M-614	14	2 1/8	13/16	13/16	13/32	1 1/16	1/2	-
12M-615	15	2 3/8	27/32	27/32	13/32	1 9/16	9/16	-
12M-616	16	2 3/8	29/32	29/32	13/32	1 15/16	19/32	-
12M-617	17	2 5/8	31/32	31/32	7/16	1 3/4	5/8	-
12M-618	18	2 5/8	1	1	7/16	1 3/4	11/16	-
12M-619	19	2 5/8	1 1/16	1 1/16	9/16	1 3/4	23/32	-
12M-620	20	2 5/8	1 1/8	1 1/8	15/32	1 3/4	3/4	-
12M-621	21	2 5/8	1 5/32	1 5/32	1/2	1 3/4	29/32	-
12M-622	22	2 7/8	1 3/16	1 3/16	1/2	1 31/32	27/32	-
12M-623	23	2 7/8	1 1/4	1 1/4	17/32	1 31/32	7/16	-
12M-624	24	2 7/8	1 5/16	1 5/16	19/32	1 31/32	29/32	-



MS-12-13H 13 Piece 3/8" Drive Deep 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
12M-607	7	12M-612	12	12M-617	17
12M-608	8	12M-613	13	12M-618	18
12M-609	9	12M-614	14	12M-619	19
12M-610	10	12M-615	15		
12M-611	11	12M-616	16		

MS-12-13H



MS-12-18H 18 Piece 3/8" Drive Deep 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
12M-607	7	12M-613	13	12M-619	19
12M-608	8	12M-614	14	12M-620	20
12M-609	9	12M-615	15	12M-621	21
12M-610	10	12M-616	16	12M-622	22
12M-611	11	12M-617	17	12M-623	23
12M-612	12	12M-618	18	12M-624	24

MS-12-18H



Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.



WILLIAMS® 3/8" HEX DRIVERS

Product Code	Size	Overall Length (Inches)	Product Code Bits	Optional Ret Ring
2MA-612	12 mm	72.7 mm	2MA-612-2	2-1XS
2MA-614	14 mm	72.7 mm	2MA-614-2	2-1XS
2A-616	1/4"	2 7/8"	2A-616-2	2-1XS
2A-618	9/16"	2 7/8"	2A-618-2	2-1XS



Features

- Designed for use with pneumatic or cordless impact guns
- Optional retaining ring ensures positive attachment to anvil
- Manufactured from special alloy steel and heat treated for optimum strength and durability
- Williams® bits are designed with a precise fit and tight tolerances to prevent slippage and disengagement
- Outperforms one-piece design models – our two-piece design makes replacement economical and convenient
- Bits can be easily replaced by hand - no need to put them in a vice and punch them out with a hammer
- Optional retaining rings available for added protection



Made in U.S.A.



2MA-614



2MA-614 with Optional
Ret Ring 2-1XS